

FIREXO 2LTR EXTINGUISHER

Name	Firexo 2LTR Extinguisher
Model/Product number	809-765-347-846
Capacity (litres)	2
Overall Product Height (mm)	415
Cylinder Height (mm)	313
Cylinder Diameter (mm)	110
Cylinder Material	Steel
Pressurizing Gas	Nitrogen
Test Pressure (bar)	30 bar
Working Pressure at 20 °C	12 bar
Weight Full (kg)	4.02
Weight Empty (kg)	1.68
Spray Range (m)	1 – 3
Discharge Time at 20 °C (seconds)	25 – 30
Temperature Range (°C)	-15°C / +60°C
Warranty	5yr
Fire Rating	13A/34B/C/D/E/25F
CE Approval	CE 0036



ALL FIRES.



METHOD OF USE

In the event of a fire hold extinguisher upright, pull out safety pin, aim at base of fire, squeeze handle and sweep side to side.

Discharge entire contents onto the fire from a 1m-3m distance.

Store upright and away from direct sunlight or heat source. Protect from frost.

Replace or recharge after use.

Tested to 35 kV for electrical fires thus suitable for use on live electrical equipment up to 1000 V at a distance of 1m.

© FIREXO 2022

This data specification sheet provides guidance only. It does not represent scientific or professional advice to any recipient or third party reader. Whilst great care has been taken to compile accurate data herein, FIREXO does not accept any responsibility or legal liability for any errors or omissions.